



Miami, FL
sales@sumawoods.com
www.sumawoods.com
305-998-7635

Flooring Underlayment Plywood

Our **Sumawood Underlayment Plywood** is stable, moisture resistant, and provides a perfect sanded surface for flooring, paneling, millwork, furniture, and cabinetry. As a subfloor, it smooths the surface, improves adhesion, and protects against moisture intrusion.

▪ HARDWOOD PLYWOOD PRODUCTS

Size:

1220 mm x 2440 mm (48" x 96")

Thickness*

5mm	1/4"	3 ply
-----	------	-------

*Although we stock standard sizes and thicknesses, we have the ability to manufacture custom products and finishes.



Grade

BB/CC Water-Resistant Underlayment Plywood

Description

- 100% Tropical hardwood plywood
- Veneers (individually) laminated with water-resistant phenolic resin glue
- Spiral cut veneer for seamless plies

Popular Name of Species	Scientific Name	Wood Density g/cm3
SUMAÚMA-BRANCA	Ceiba Pentandra	0,353
COPAIBA	Multijuga	0,642
COPAIBA	Langsdorffi	0,61
GUARIBEIRO	Phyllocarpus riedelli	0,4
ANGICO	Parkia nitida	0,68
PINHO-CUIABANO	Schizolobium amazonicum	0,49

Certifications

- Forest Stewardship Council **FSC STD 40-004V3-0** (Chain of Custody Certification)
- **CARB ATCM 93120**
- **EPA TSCA Title VI**

Applications

- Water-resistant flooring underlayment
- For use with all types of floor coverings
- For use in kitchens, bathrooms, and laundry rooms
- Ideal for shelving, cabinetry, underlayment, paneling, furniture, and millwork
- Any other applications where a non-structural, uniform sanded surface is necessary

Packaging Details

Thickness	Pieces per Bundle	Volume in m3	Pounds per Unit
5mm / 1/4"	180	501	Between 3200-3400 lbs/bundle